

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number  
**WO 2004/052052 A2**

(51) International Patent Classification<sup>7</sup>: **H04S 1/00**

(21) International Application Number:  
PCT/EP2003/013172

(22) International Filing Date:  
24 November 2003 (24.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
02026779.5 2 December 2002 (02.12.2002) EP

(71) Applicant (for all designated States except US): **THOMSON LICENSING S.A.** [FR/FR]; 46, Quai Alphonse le Gallo, F-92100 Boulogne Billancourt (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SCHMIDT, Jürgen**

[DE/DE]; Akazienstr. 5b, 31515 Wunstorf (DE). **SPILLE, Jens** [DE/DE]; Kleines Feld 58, 30966 Hemmingen (DE). **SCHRÖDER, Ernst, F.** [DE/DE]; Pinkenburger Str. 25D, 30655 Hannover (DE). **BÖHM, Johannes** [DE/DE]; Akazienweg 54, 37083 Göttingen (DE).


(74) Agent: **HARTNACK, Wolfgang**; Deutsche Thomson-Brandt GmbH, European Patent Operations, Karl-Wiechert-Allee 74, 30625 Hannover (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR PROCESSING TWO OR MORE INITIALLY DECODED AUDIO SIGNALS RECEIVED OR REPLAYED FROM A BITSTREAM



(57) Abstract: In the MPEG-4 standard ISO/IEC 14496:2001 several audio objects that can be coded with different MPEG-4 format coding types can together form a composed audio system representing a single soundtrack from the several audio substreams. In a receiver the multiple audio objects are decoded separately, but not directly played back to a listener. Instead, transmitted instructions for mixdown are used to prepare a single soundtrack. Mixdown conflicts can occur in case the audio signals to be combined have different channel numbers or configurations. According to the invention an additional audio channel configuration node is used that tags the correct channel configuration information items to the decoded audio data streams to be presented. The invention enables the content provider to set the channel configuration in such a way that the presenter at receiver side can produce a correct channel presentation under all circumstances. An escape code value in the channel configuration data facilitates correct handling of not yet defined channel combinations.



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,  
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,  
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *without international search report and to be republished upon receipt of that report*